

Index for Stsadm operations and properties (Office SharePoint Server)

In this article:

- [Operations](#)
- [Properties](#)

Operations

| Name | Description | More information |
|--|---|---|
| Activatefeature | Activates a feature in the feature collection. | Activatefeature: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262692(printer).aspx] |
| Addalternatedomain | Adds an internal URL and maps it to one of the five URL zones of a Web application or external resource. | Addalternatedomain: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263437(printer).aspx] |
| Addcontentdb | Creates a new content database or adds a database that needs to be upgraded when the url and databasename parameters are specified. | Addcontentdb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263422(printer).aspx] |
| Adddataconnectionfile | Adds a new DataConnectionFile to the DataConnectionFiles collection for InfoPath Forms Services. | Adddataconnectionfile: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263067(printer).aspx] |
| Add-ecsfiletrustedlocation | Lets an administrator add a file to the trusted location list. | Add-ecsfiletrustedlocation: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262818(printer).aspx] |
| Add-ecssafedataprotider | Lets an administrator add a supported provider type to the safe provider list. | Add-ecssafedataprotider: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263293(printer).aspx] |
| Add-ecstrusteddataconnectionlibrary | Adds a trusted data connection to a library. | Add-ecstrusteddataconnectionlibrary: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261726(printer).aspx] |
| Add-ecsuserdefinedfunction | Adds a user defined function. | Add-ecsuserdefinedfunction: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262904(printer).aspx] |
| Addexemptuseragent | Adds a user agent, which is typically in the form of a search bot, to receive the XML file that contains the data of the form for indexing instead of the HTML rendering of the form. | Addexemptuseragent: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261990(printer).aspx] |
| Addpath | Adds a managed path inclusion to a Web application. | Addpath: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263161(printer).aspx] |
| Addpermissionpolicy | Adds a user to a policy role for the Web application based on the specified permission level name and corresponding zone. | Addpermissionpolicy: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262826(printer).aspx] |
| Addsolution | Adds a solution file to the solution store. | Addsolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263162(printer).aspx] |
| Addtemplate | Adds a site template to the template gallery. | Addtemplate: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261822(printer).aspx] |
| Adduser | Adds a user account to the specified site collection and assigns it to the specified site group. | Adduser: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262627(printer).aspx] |
| Addwppack | Adds a Web Part package to the server Web Part gallery. | Addwppack: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263164(printer).aspx] |
| Addzoneurl | Configures the public URL and maps it to one of the five URL zones of a Web application or external | Addzoneurl: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263164(printer).aspx] |

| | | |
|-------------------------------------|--|--|
| | resource. | us/library/cc261980(printer).aspx] |
| Allowuserformwebserviceproxy | Determines whether a user form template (that is, a non-administrator deployed form template published to a content type or a document library) can use the proxy. | Allowuserformwebserviceproxy: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263232(printer).aspx] |
| Allowwebserviceproxy | Turns on or off the Web service proxy for the specified Web application. | Allowwebserviceproxy: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263132(printer).aspx] |
| Authentication | Authentication provides the user identity input to the authorization process which determines what actions the current user is allowed to perform on a given object. | Authentication: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263116(printer).aspx] |
| Backup | Describes how to back up a site collection, an individual database, a Web application, or an entire farm. | <ul style="list-style-type: none"> • Backup: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263441(printer).aspx] • Back up Office SharePoint Server 2007 by using built-in tools [http://technet.microsoft.com/en-us/library/cc263298(printer).aspx] |
| Backuphistory | Displays a history of backup and restore operations that have been run. | Backuphistory: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262993(printer).aspx] |
| Binddrsvice | Registers a data retrieval service adapter. | Binddrsvice: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263415(printer).aspx] |
| Blockedfilelist | Enables an administrator to add or delete a file type to the blocked file types list for a Web application. | Blockedfilelist: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263481(printer).aspx] |
| Changepermissionpolicy | Updates the Web application policy level for a user to enable a change to specific permission levels the user is assigned. | Changepermissionpolicy: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263147(printer).aspx] |
| Copyappbincontent | Copies Web application-specific files, such as page resource (*.resx) files from their respective locations in the 12\CONFIG folder to the correct location in each Web application on the computer. | Copyappbincontent: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261996(printer).aspx] |
| Createadminvs | Displays the port number to the SharePoint Central Administration Web site. | Createadminvs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263190(printer).aspx] |
| Createcsmigrationprofile | Creates a migration profile by providing a profile name, database server name, database name, and database user name. | Createcsmigrationprofile: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263272(printer).aspx] |
| Creategroup | Lets site collection administrators create new groups from any site collection. | Creategroup: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263302(printer).aspx] |
| Createsite | Creates a site collection at the specified Uniform Resource Locator (URL) with the specified user as site collection owner and site collection administrator. | Createsite: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262594(printer).aspx] |
| Createsiteinnewdb | Creates a site at the specified Uniform Resource Locator (URL) and creates a new content database using the user name and password you specify. | Createsiteinnewdb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262407(printer).aspx] |
| Createssp | Creates a new Shared Services Provider (SSP) in the farm. | Createssp: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262773(printer).aspx] |
| Createweb | Creates a subsite at the specified Uniform Resource Locator (URL). | Createweb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262913(printer).aspx] |
| Dataserepair | Detects and removes orphaned items from content databases in Windows SharePoint Services. | Databaserepair: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263282(printer).aspx] |

| | | |
|---------------------------------|---|--|
| Deactivatefeature | Deactivates a feature in the feature collection. | Deactivatefeature: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262680(printer).aspx] |
| Deleteadminvs | Unprovisions the SharePoint Central Administration Web site from the local machine. | Deleteadminvs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262408(printer).aspx] |
| Deletealternatedomain | Deletes an internal URL from a URL zone. | Deletealternatedomain: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263056(printer).aspx] |
| Deletecsmigrationprofile | Deletes the named migration profile. | Deletecsmigrationprofile: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263171(printer).aspx] |
| Deleteconfigdb | Unprovisions the local machine from the farm and deletes the configuration database (but does not drop the configuration database). | Deleteconfigdb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263385(printer).aspx] |
| Deletecontentdb | Detaches a content database when the Web application, database name, and database server are specified. | Deletecontentdb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262449(printer).aspx] |
| Deletegroup | Deletes a group created in Microsoft Office SharePoint Server 2007. | Deletegroup: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262002(printer).aspx] |
| Deletepath | Removes an included path from the list of paths managed by Windows SharePoint Services. | Deletepath: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424945(printer).aspx] |
| Deletepermissionpolicy | Deletes a permission policy for a user from the site collection by specifying the URL name and user login. | Deletepermissionpolicy: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263488(printer).aspx] |
| Deletesite | Deletes the site collection with the specified URL from the Web application. | Deletesite: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261873(printer).aspx] |
| Deletesolution | Removes a Windows SharePoint Services Solution Package (*.wsp) from the solution store. | Deletesolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261929(printer).aspx] |
| Deletessp | Deletes a Shared Services Provider (SSP) in a Web application when the title parameter is specified. | Deletessp: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263248(printer).aspx] |
| Deletessptimerjob | Deletes all of the timer jobs in the Shared Services Provider (SSP). | Deletessptimerjob: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262978(printer).aspx] |
| Deletetemplate | Deletes a specified site template from the site template gallery. | Deletetemplate: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263068(printer).aspx] |
| Deleteuser | Deletes a user account from the specified site collection and specified site. | Deleteuser: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262836(printer).aspx] |
| Deleteweb | Deletes a subsite using the specified Uniform Resource Locator (URL). | Deleteweb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262877(printer).aspx] |
| Deletewppack | Removes the Web Parts in a Web Part package from a virtual server. | Deletewppack: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263364(printer).aspx] |
| Deletezoneurl | Deletes a public URL and the zone to which it is mapped. | Deletezoneurl: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262661(printer).aspx] |
| Deploysolution | Deploys files related to a solution from the configuration database to individual front-end Web servers in the farm. | Deploysolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262459(printer).aspx] |

| | | |
|---|---|--|
| Deploywppack | Deploys a Web Part package. | Deploywppack: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263466(printer).aspx] |
| Disablescc | Disables Self-Service Site Creation for the specified Web application. | Disablescc: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261994(printer).aspx] |
| Displaysolution | Displays specific solution or Web Part information in a solution store. | Displaysolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262211(printer).aspx] |
| Editcmsmigrationprofile | Edits a migration profile by providing a profile name, database server name, database name, and database user name. | Editcmsmigrationprofile: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262428(printer).aspx] |
| Editcontentdeploymentpath | Edits and manages a content deployment path. | Editcontentdeploymentpath: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262814(printer).aspx] |
| Editssp | Allows the site collection administrator for the Shared Services Administration site to perform the following functions: <ul style="list-style-type: none"> • Change the databases that a Shared Services Provider (SSP) uses. • Change the SQL credentials associated with the SSP databases. • Modify the service account credentials. • Rename an SSP. | Editssp: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262727(printer).aspx] |
| Enablecmsurlredirect | Activates the Uniform Resource Locator (URL) redirection feature for URLs in Microsoft Content Management Server 2002. | Enablecmsurlredirect: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263184(printer).aspx] |
| Enablescc | Enables Self-Service Site Creation for the specified Web application. | Enablescc: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262479(printer).aspx] |
| Enumalternatedomains | Lists the internal URLs and specifies the URL zones and public URLs to which they are mapped. | Enumalternatedomains: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263292(printer).aspx] |
| Enumcontentdbs | Enumerates all content databases in the Web application. | Enumcontentdbs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262488(printer).aspx] |
| Enumdataconnectionfiledependants | Enumerates all form that are dependent on the specified data connection file. | Enumdataconnectionfiledependants: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262850(printer).aspx] |
| Enumdataconnectionfiles | Enumerates all of the DataConnectionFiles in the collection in alphabetical order. | Enumdataconnectionfiles: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262127(printer).aspx] |
| Enumdeployments | Enumerates all pending and active deployments in the farm. | Enumdeployments: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263253(printer).aspx] |
| Enumemptuseragents | Returns the rendering content of the form as an XML instead HTML. | Enumemptuseragents: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262712(printer).aspx] |
| Enumformtemplates | Lists the administrator-deployed form templates on the farm. | Enumformtemplates: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262165(printer).aspx] |
| Enumgroups | Lists all the groups in Microsoft Office SharePoint Server 2007. | Enumgroups: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262755(printer).aspx] |
| Enumroles | Lists the site groups that are available for use in a particular site or subsite. | Enumroles: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262755(printer).aspx] |

| | | |
|--------------------------------------|--|---|
| | | us/library/cc263251(printer).aspx] |
| Enumservices | Lists all the services in the Web application within a farm. | Enumservices: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262678(printer).aspx] |
| Enumsites | Displays a list of sites that are hosted in a Web application. To find the sites that need to be upgraded, use the redirectedsites parameter. | Enumsites: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262492(printer).aspx] |
| Enumsolutions | Enumerates the list of Windows SharePoint Services Solution Package (*.wsp) and Web Part packages located in the solution store of the farm. | Enumsolutions: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263381(printer).aspx] |
| Enumssp | Lists all the details of the Shared Services Providers (SSPs) in the farm or of a single SSP. | Enumssp: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262077(printer).aspx] |
| Enumssptimerjobs | Enumerates all of the timer jobs in the Shared Services Provider (SSP). | Enumssptimerjobs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262694(printer).aspx] |
| Enumsubwebs | Lists the subsites that have been created immediately below a particular site. | Enumsubwebs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263243(printer).aspx] |
| Enumtemplates | Lists the site templates that have been submitted to the global site template catalog. | Enumtemplates: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263342(printer).aspx] |
| Enumusers | Lists the users of a particular site collection or subsite. | Enumusers: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263220(printer).aspx] |
| Enumwppacks | Lists the Web Part packages currently in the server Web Part gallery. | Enumwppacks: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262761(printer).aspx] |
| Enumzoneurls | Lists all of the public URL and the zones to which they are mapped. | Enumzoneurls: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262774(printer).aspx] |
| Email | Sets the e-mail configuration settings for your server. | Email: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261681(printer).aspx] |
| Execadmsvcjobs | Permits a user to run any administrative service job in which the Windows SharePoint Services Administration (SPAdmin) service has been disabled. | Execadmsvcjobs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262783(printer).aspx] |
| Export | Exports site and subsite data from your Microsoft Office SharePoint Server 2007 installation. | Export: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262759(printer).aspx] |
| Extendvs | Extends a Windows SharePoint Services 3.0 Web application and creates a new content database. | Extendvs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263040(printer).aspx] |
| Extendvsinwebfarm | Extends a Windows SharePoint Services 3.0 Web application for use in a server farm | Extendvsinwebfarm: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262329(printer).aspx] |
| Forcedeletelist | Allows a user to delete a list that might appear to be in a corrupted state. | Forcedeletelist: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262609(printer).aspx] |
| Formtemplatequiescestatus | Displays the status of the quiesce process of a form template. | Formtemplatequiescestatus: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263193(printer).aspx] |
| Getadminport | Returns the administration port for Windows SharePoint Services. | Getadminport: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261984(printer).aspx] |
| Getdataconnectionfileproperty | Displays the file property of each data connection file in the store of InfoPath Forms Services. | Getdataconnectionfileproperty: Stsadm operation (Office SharePoint Server) |

| | | |
|---|--|---|
| | | [http://technet.microsoft.com/en-us/library/cc263392(printer).aspx] |
| Getformtemplateproperty | Retrieves properties on individual InfoPath Form Services templates. | Getformtemplateproperty: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262940(printer).aspx] |
| Getsitedirectoryscanschedule | Displays the current schedule of all site directory links scan jobs to be run. | Getsitedirectoryscanschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262859(printer).aspx] |
| Getsitelock | Retrieves the lock status of a site. | Getsitelock: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262915(printer).aspx] |
| Import | Imports site and subsite data from your Microsoft Office SharePoint Server 2007 installation. | Import: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261866(printer).aspx] |
| Installfeature | Installs a feature. | Installfeature: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263123(printer).aspx] |
| Listlogginglevels | Lists the current event log and trace log logging levels for each diagnostic logging category that is registered in a farm. | Listlogginglevels: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262133(printer).aspx] |
| Listregisteredsecuritytrimmers | Lists all registered security trimmers in the farm. | Listregisteredsecuritytrimmers: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262938(printer).aspx] |
| Localupgradestatus | Displays the farm and local server components that need to be upgraded. | Localupgradestatus: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263319(printer).aspx] |
| Managepermissionpolicylevel | Enables an administrator to manage the policy levels for a Web application. | Managepermissionpolicylevel: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263387(printer).aspx] |
| Mergecontentdbs | Permits a site collection to be moved from one content database to another when the source databasename and destination databasename parameters are specified. | Mergecontentdbs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262923(printer).aspx] |
| Migrateuser | Migrates a user account in Windows SharePoint Services 3.0 to a new user name and binary ID. | Migrateuser: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262141(printer).aspx] |
| Osearch | Manages the Office SharePoint Server Search service. | Osearch: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262920(printer).aspx] |
| Osearchdiacriticsensitive | Enables or disables the diacritic sensitivity setting. | Osearchdiacriticsensitive: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262590(printer).aspx] |
| Peoplepicker-getsiteuseraccountdirectorypath | Retrieves the user account directory path setting for the site collection. | Getsiteuseraccountdirectorypath: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262912(printer).aspx] |
| Peoplepicker-setsiteuseraccountdirectorypath | Sets the site user account directory path to a specific Organizational Unit (OU) in the same domain when the url and path parameters are specified. | Setsiteuseraccountdirectorypath: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263328(printer).aspx] |
| Preparetomove | Prepares sites and content databases before moving to a new Web application by setting up the profile and membership synchronization service. | Preparetomove: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262122(printer).aspx] |
| Profilechangelog | Maintains a change log that records the changes made to the user profiles. | Profilechangelog: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263013(printer).aspx] |
| Profiledeletehandler | Gives an administrator a chance to run a workflow when a user is about to be deleted. | Profiledeletehandler: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263114(printer).aspx] |

| | | |
|---|---|--|
| Provisionservice | Starts or stops the SPService on the local computer or a custom service. | Provisionservice: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262031(printer).aspx] |
| Quiescefarm | Temporarily suspends the farm's ability to accept new sessions that are essential to rendering infopath forms on a server. | Quiescefarm: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262797(printer).aspx] |
| Quiescefarmstatus | Displays the quiesce status of the server farm. | Quiescefarmstatus: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262924(printer).aspx] |
| Quiesceformtemplate | Temporarily takes a form template offline. | Quiesceformtemplate: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263354(printer).aspx] |
| Reconvertallformtemplates | Upgrades the form template cached data to run on the upgraded server. | Reconvertallformtemplates: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262763(printer).aspx] |
| Refreshdms | Refreshes the Directory Management Service if a database is restored or moved to a location where the incoming e-mail settings are not correct. | Refreshdms: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262558(printer).aspx] |
| Refreshsitedms | Performs the same function as the Refreshdms operation but on a site collection level. | Refreshsitedms: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263418(printer).aspx] |
| Registersecuritytrimmer | Enterprise Search in Microsoft Office SharePoint Server 2007 performs security trimming of search results at query time. | Registersecuritytrimmer: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263124(printer).aspx] |
| Registerwsswriter | Enables the Windows SharePoint Services VSS Writer service (known as WSS Writer service) on any front-end Web server. | Registerwsswriter: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262819(printer).aspx] |
| Removedataconnectionfile | Removes all DataConnectionFiles from the DataConnectionFiles collection. | Removedataconnectionfile: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263188(printer).aspx] |
| Removedrservice | Removes a data retrieval service from the list of data retrieval services. | Removedrservice: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261886(printer).aspx] |
| Remove-ecsfiletrustedlocation | Lets an administrator remove a file from the trusted location list. | Remove-ecsfiletrustedlocation: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262602(printer).aspx] |
| Remove-ecssafedataprotider | Lets an administrator remove a supported provider type to the safe provider list. | Remove-ecssafedataprotider: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263119(printer).aspx] |
| Remove-ecstrusteddataconnectionlibrary | Removes a trusted data connection from a library. | Remove-ecstrusteddataconnectionlibrary: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262027(printer).aspx] |
| Remove-ecsuserdefinedfunction | Removes a user-defined function from Excel Calculation Services. | Remove-ecsuserdefinedfunction: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262202(printer).aspx] |
| Removeexemptuseragent | Removes a user agent, which is typically in the form of a search bot, from the ExemptUserAgent collection. | Removeexemptuseragent: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263015(printer).aspx] |
| Removesolutiondeploymentlock | Removes the solution deployment lock for the specified server or all servers from the back-end database. | Removesolutiondeploymentlock: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262463(printer).aspx] |
| Renameserver | Changes the name of the specified server in the configuration database. | Renameserver: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263117(printer).aspx] |
| | Changes a URL of a host-named site collection to a | Renamesite: Stsadm operation (Office SharePoint |

| | | |
|--|--|--|
| Renamesite | new URL. | Server [http://technet.microsoft.com/en-us/library/cc263038(printer).aspx] |
| Renameweb | Changes the URL of a subsite. | Renameweb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263508(printer).aspx] |
| Restore | Explains how a restoration of a site collection, an individual database, a Web application, or an entire farm is performed. | Restore: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262087(printer).aspx] |
| Restoressp | Creates a Shared Service Provider using a restored database. | Restoressp: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262163(printer).aspx] |
| Retractsolution | Retracts the specified solution's deployment, and removes files from the front-end Web server. | Retractsolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261799(printer).aspx] |
| Retractwppack | Retracts the deployment of a specified Web Part package. | Retractwppack: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262063(printer).aspx] |
| Runcmsmigrationprofile | Runs a named migration profile. The profile name is the only required parameter. | Runcmsmigrationprofile: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263498(printer).aspx] |
| Runcontentdeploymentjob | Runs a named deployment job. | Runcontentdeploymentjob: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263029(printer).aspx] |
| Scanforfeatures | Scans for new features in the file system, and if new features are present, installs them. | Scanforfeatures: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263234(printer).aspx] |
| Setadminport | Changes the default zone Uniform Resource Locator (URL) and/or application pool located on the SharePoint Central Administration Web site. | Setadminport: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262249(printer).aspx] |
| Setbulkworkflowtaskprocessingschedule | Sets the schedule for when tasks are processed by using the Process all tasks option. | Setbulkworkflowtaskprocessingschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262875(printer).aspx] |
| Setconfigdb | Creates a new configuration database in a farm or joins the local computer to an existing farm's configuration database. | Setconfigdb: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261712(printer).aspx] |
| Setcontentdeploymentjobschedule | Enables the user to create an advanced schedule to run a deployment job. | Setcontentdeploymentjobschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263273(printer).aspx] |
| Setdataconnectionfileproperty | Sets a file property to a data connection file in the store of InfoPath Forms Services. | Setdataconnectionfileproperty: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262828(printer).aspx] |
| Setdefaultssp | Sets a Shared Services Provider (SSP) as the default SSP in a farm. | Setdefaultssp: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263296(printer).aspx] |
| Set-ecsexternaldata | Lets an administrator set an external data connection to Excel Calculation Services. | Set-ecsexternaldata: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263170(printer).aspx] |
| Set-ecslloadbalancing | Lets an administrator define load balancing for Excel Calculation Services. | Set-ecslloadbalancing: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263083(printer).aspx] |
| Set-ecsmemoryutilization | Lets an administrator determine memory allocation for Excel Calculation Services. | Set-ecsmemoryutilization: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263189(printer).aspx] |
| Set-ecsecurity | Lets an administrator set security settings for Excel Calculation Services. | Set-ecsecurity: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263284(printer).aspx] |

| | | |
|-------------------------------------|--|--|
| Set-ecsessionmanagement | Lets an administrator set session management settings for Excel Calculation Services. | Set-ecsessionmanagement: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262960(printer).aspx] |
| Set-ecsworkbookcache | Lets an administrator set workbook cache settings on disk and in memory for Excel Calculation Services. | Set-ecsworkbookcache: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262053(printer).aspx] |
| Setformtemplateproperty | Sets the properties of an individual form template. | Setformtemplateproperty: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261694(printer).aspx] |
| Setholdschedule | Sets the schedule to process all records that are on hold (records whose retention schedules are suspended). | Setholdschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263177(printer).aspx] |
| Setlogginglevel | Sets the Windows event log and trace log logging level for one or more diagnostic logging categories registered in the farm. | Setlogginglevel: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261740(printer).aspx] |
| Setpolicyschedule | Sets the schedule for processing changes to a policy on the items that are impacted by that policy. | Setpolicyschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262865(printer).aspx] |
| Setrecordsrepositoryschedule | Sets the schedule to process all records that have been submitted to Records Center sites in the farm. | Setrecordsrepositoryschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263456(printer).aspx] |
| Setsearchandprocessschedule | Sets the schedule for when the search and process timer job runs. | Setsearchandprocessschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262651(printer).aspx] |
| Setsitedirectoryscanschedule | Sets a schedule for a job to run the site directory links scan. | Setsitedirectoryscanschedule: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262862(printer).aspx] |
| Setsitelock | Sets a value that specifies whether the site collection is locked and unavailable for read or write access. | Setsitelock: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262811(printer).aspx] |
| Setssport | Updates the port or ports for the shared Microsoft Internet Information Services (IIS) Web site, "Office Server Web Services", which used by Microsoft Office SharePoint Server 2007 Web services. | Setssport: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261670(printer).aspx] |
| Setworkflowconfig | Enables or disables the workflow settings. | Setworkflowconfig: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262767(printer).aspx] |
| Siteowner | Sets the primary or secondary administrator of a site collection. | Siteowner: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262637(printer).aspx] |
| Sync | Configures the Windows SharePoint Services 3.0 synchronization job. Normally, this operation is used in conjunction with the preparetomove operation | Sync: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263196(printer).aspx] |
| Syncsolution | Performs a synchronization of the Windows SharePoint Services Solution Package (WSP) solutions stored in the configuration database with the files stored on disk. | Syncsolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262688(printer).aspx] |
| Tzmove | Allows an administrator to update data that is affected by a change in the start and/or end of Daylight Saving time (DST). | Tzmove: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263472(printer).aspx] |
| Unextendvs | Removes Windows SharePoint Services 3.0 from a particular Web application. | Unextendvs: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262863(printer).aspx] |
| Uninstallfeature | Removes the specified feature definition from the collection of feature definitions in the farm. | Uninstallfeature: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262976(printer).aspx] |
| Unquiescefarm | Resumes the farm's ability to accept new sessions that are essential to rendering InfoPath forms on a | Unquiescefarm: Stsadm operation (Office SharePoint Server) |

| | | |
|------------------------------------|--|---|
| | server. | [http://technet.microsoft.com/en-us/library/cc261750(printer).aspx] |
| Unquiesceformtemplate | Restores a specific form template for use on the server. | Unquiesceformtemplate: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263346(printer).aspx] |
| Unregistersecuritytrimmer | Unregisters a custom security trimmer when the ssp and id parameters are specified. | Unregistersecuritytrimmer: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262354(printer).aspx] |
| Unregisterwsswriter | Disables the Windows SharePoint Services VSS Writer service (known as WSS Writer service) on any front-end Web server. | Unregisterwsswriter: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262416(printer).aspx] |
| Updateaccountpassword | Updates the Web application pool passwords. | Updateaccountpassword: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262549(printer).aspx] |
| Updatefarmcredential | Updates the Web application pool for the SharePoint Central Administration Web site and the Windows SharePoint Services Timer service (SPTimer). | Updatefarmcredentials: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262150(printer).aspx] |
| Upgrade | Upgrades the specified site collection during a gradual upgrade. | Upgrade: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263413(printer).aspx] |
| Upgradesolution | Upgrades an existing solution. The solution to be upgraded could be either deployed or not deployed; however, the immediate or time parameters apply only if the solution has been deployed. | Upgradesolution: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262014(printer).aspx] |
| Upgradetargetwebapplication | Prepares the environment for the gradual upgrade of a specific version 2.0 Web application by moving the existing version 2.0 Web application to a new URL and making a new version 3.0 Web application that is based on the existing version 2.0 Web application and associated settings. | Upgradetargetwebapplication: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263323(printer).aspx] |
| Userrole | Adds or deletes permission levels to site groups. | Userrole: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262083(printer).aspx] |
| Verifyformtemplate | Verifies that the form template can be browser-enabled. | Verifyformtemplate: Stsadm operation (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263085(printer).aspx] |

Properties

| Property name | Description | More information |
|------------------------------|---|---|
| Alerts-enabled | Turns alerts on or off. | Alerts-enabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263206(printer).aspx] |
| Alerts-limited | Specifies the number of alerts to which a user can create. | Alerts-limited: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263016(printer).aspx] |
| Alerts-maximum | Specifies the maximum number of alerts a user can create. | Alerts-maximum: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262842(printer).aspx] |
| Avallowdownload | Specifies whether users can download infected documents to their local computers. | Avallowdownload: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262824(printer).aspx] |
| Avcleaningenabled | Specifies whether antivirus cleaning is enabled or disabled. | Avcleaningenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262203(printer).aspx] |
| Avdownloadscanenabled | Specifies whether documents are scanned when they are downloaded. | Avdownloadscanenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262830(printer).aspx] |
| Avnumberofthreads | Specifies the number of threads to use for antivirus processes. | Avnumberofthreads: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263246(printer).aspx] |
| Avtimeout | Specifies how long to wait before | Avtimeout: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263246(printer).aspx] |

| | | |
|--|--|---|
| | an antivirus process times out. | us/library/cc262745(printer).aspx] |
| Avuploadscanenabled | Specifies whether documents are scanned when they are uploaded. | Avuploadscanenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263294(printer).aspx] |
| Change-log-expiration-enabled | Specifies whether change logs are deleted after the time span defined in the Change-log-retention-period: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261921(printer).aspx] property. | Change-log-expiration-enabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263361(printer).aspx] |
| Change-log-retention-period | Specifies the amount of time to preserve change logs | Change-log-retention-period: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261921(printer).aspx] |
| Command-line-upgrade-running | Specifies whether the upgrade process has already been started. | Command-line-upgrade-running: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263303(printer).aspx] |
| Data-retrieval-services-enabled | Turns data retrieval services on or off. | Data-retrieval-services-enabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262065(printer).aspx] |
| Data-retrieval-services-inherit | Specifies whether the Web application inherits data retrieval service settings that are located on the SharePoint Central Administration Web site. | Data-retrieval-services-inherit: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261997(printer).aspx] |
| Data-retrieval-services-oledb-providers | Obsolete. | Not applicable |
| Data-retrieval-services-response-size | Specifies the response size of the data source that is returned to the data retrieval service. | Data-retrieval-services-response-size: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262145(printer).aspx] |
| Data-retrieval-services-timeout | Specifies the request time out setting. | Data-retrieval-services-timeout: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263490(printer).aspx] |
| Data-retrieval-services-update | Turns the support for update queries on or off. | Data-retrieval-services-update: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262008(printer).aspx] |
| Data-source-controls-enabled | Turns the data source controls on the server on or off. | Data-source-controls-enabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262352(printer).aspx] |
| Database-command-timeout | Retrieves or sets the wait time before terminating the attempt to execute a command and generating an error. | Database-command-timeout: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263515(printer).aspx] |
| Database-connection-timeout | Retrieves an open connection or sets a connection to a Microsoft SQL Server database. | Database-connection-timeout: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263314(printer).aspx] |
| Days-to-show-new-icon | Specifies the number of days to display the "New" icon for items added to a Web site. | Days-to-show-new-icon: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262903(printer).aspx] |
| Dead-site-auto-delete | Turns on or off the setting to delete the site collection | Dead-site-auto-delete: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262131(printer).aspx] |
| Dead-site-notify-after | Specifies the number of days to wait before sending notifications | Dead-site-notify-after: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262143(printer).aspx] |
| Dead-site-num-notifications | Specifies the number of notifications to send | Dead-site-num-notifications: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263393(printer).aspx] |
| Defaultquotatemplate | Specifies the default quota template to be used when creating new site collection on a specified Web application. | Defaultquotatemplate: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262171(printer).aspx] |
| Defaulttimezone | Specifies the time zone for sites that are created in a Web | Defaulttimezone: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en- |

| | | |
|--|--|---|
| | application. | us/library/cc263095(printer).aspx] |
| Delete-web-send-email | Deletes the site collection if use is not confirmed | Delete-web-send-email: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263091(printer).aspx] |
| Irmaddinsenabled | Specifies a rights management platform other than Windows Rights Management Server. | Irmaddinsenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261802(printer).aspx] |
| Irmrmscertserver | Specifies the location of the Windows Rights Management Services server. | Irmrmscertserver: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263355(printer).aspx] |
| Irmrmsenabled | Controls whether the server should use the Windows RMS infrastructure instead of another rights management platform. | Irmrmsenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262390(printer).aspx] |
| Irmrmsusead | Specifies that Microsoft Office SharePoint Server 2007 should use the location of the RMS server that is stored in Active Directory, rather than an administrator manually specifying the location of the Windows RMS. | Irmrmsusead: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263152(printer).aspx] |
| Job-ceip-datacollection | Specifies the time schedule for when Customer Experience Improvement Program (CEIP) data is collected. | Job-ceip-datacollection: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424940(printer).aspx] |
| Job-change-log-expiration | Specifies the time schedule when the change log timer job occurs. | Job-change-log-expiration: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424949(printer).aspx] |
| Job-config-refresh | Specifies the schedule for the configuration refresh job. | Job-config-refresh: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424971(printer).aspx] |
| Job-database-statistics | Specifies the time schedule when database statistics are collected. | Job-database-statistics: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424963(printer).aspx] |
| Job-dead-site-delete | Specifies the frequency interval and time range to delete unused Web sites automatically, for example, "Weekly at Sat 0:00:00". | Job-dead-site-delete: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261868(printer).aspx] |
| Job-immediate-alerts | Specifies the frequency to check for alerts that are to be sent immediately. | Job-immediate-alerts: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262432(printer).aspx] |
| Job-recycle-bin-cleanup | Specifies the time schedule for a cleanup of the Recycle Bin to occur. | Job-recycle-bin-cleanup: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424969(printer).aspx] |
| Job-usage-analysis | Lets an administrator set the time interval for usage processing. | Job-usage-analysis: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262126(printer).aspx] |
| Job-watson-trigger | Displays the time schedule of the Windows SharePoint Services Watson Upload job. | Job-watson-trigger: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424957(printer).aspx] |
| Job-workflow | Sends the workflow events that have been queued and delivers them to workflows. | Job-workflow: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424970(printer).aspx] |
| Job-workflow-autoclean | Specifies the time schedule for when a scan occurs to delete workflow instance data. | Job-workflow-autoclean: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424968(printer).aspx] |
| Job-workflow-failover | Specifies a schedule for restarting workflow operations that fail because of external reasons. | Job-workflow-failover: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc424943(printer).aspx] |
| Large-file-chunk-size | Specifies the amount of data that can be read from the server running Microsoft SQL Server at one time. | Large-file-chunk-size: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262061(printer).aspx] |
| Max-file-post-size | Specifies the maximum allowable size for a single upload of content to any site. | Max-file-post-size: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261801(printer).aspx] |
| Peoplepicker-activedirectorysearchtimeout | Configures the timeout when a | Peoplepicker-activedirectorysearchtimeout: Stsadm |

| | | |
|---|---|---|
| | query is issued to Active Directory. | property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263496(printer).aspx] |
| Peoplepicker-distributionlistsearchdomains | Restricts the search of a distribution list to a specific subset of domains. | Peoplepicker-distributionlistsearchdomains: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263255(printer).aspx] |
| Peoplepicker-nowindowsaccountsforonwindowsauthenticationmode | Specifies not to search Active Directory when the current port is using forms-based authentication. | Peoplepicker-nowindowsaccountsforonwindowsauthenticationmode: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263264(printer).aspx] |
| Peoplepicker-onlysearchwithinsitecollection | Displays only users that are members of the site collection. | Peoplepicker-onlysearchwithinsitecollection: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261988(printer).aspx] |
| Peoplepicker-searchadcustomfilter | Enables a farm administrator to specify a unique search query. | Peoplepicker-searchadcustomfilter: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263452(printer).aspx] |
| Peoplepicker-searchadcustomquery | Permits the administrator to set the custom query that is sent to Active Directory. | Peoplepicker-searchadcustomquery: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262988(printer).aspx] |
| Peoplepicker-searchadforests | Permits a user to search from a second one-way trusted forest or domain. | Peoplepicker-searchadforests: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263460(printer).aspx] |
| Peoplepicker- serviceaccountdirectorypaths | Enables a farm administrator to manage the site collection that has a specific organizational unit (OU) setting defined. | Peoplepicker-serviceaccountdirectorypaths: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263012(printer).aspx] |
| Presenceenabled | Allows users of a SharePoint site to see if other users are online and send instant messages to them. | Presenceenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262782(printer).aspx] |
| Recycle-bin-cleanup-enabled | Specifies whether a cleanup to the recycle bin occurs. | Recycle-bin-cleanup-enabled: Stsadm properties (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263200(printer).aspx] |
| Recycle-bin-enabled | Turns the Recycle Bin on or off. | Recycle-bin-enabled: Stsadm properties (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261974(printer).aspx] |
| Recycle-bin-retention-period | Specifies the retention period, in days, of deleted items in the Recycle Bin. | Recycle-bin-retention-period: Stsadm properties (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262418(printer).aspx] |
| Second-stage-recycle-bin-quota | Specifies how much hard disk space is available to a second stage Recycle Bin as a percentage of the quota allotted to the Web application. | Second-stage-recycle-bin-quota: Stsadm properties (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261839(printer).aspx] |
| Token-timeout | Specifies the amount of time before a user token times out. | Token-timeout: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263377(printer).aspx] |
| Usageprocessingenabled | Configures whether the usage analysis process is turned on or off. | Usageprocessingenabled: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263216(printer).aspx] |
| Workflow-cpu-throttle | Obsolete. | Not applicable |
| Workflow-eventdelivery-batchsize | Specifies the maximum number of work items that will be paged in to a processing timer job. | Workflow-eventdelivery-batchsize: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc261828(printer).aspx] |
| Workflow-eventdelivery-throttle | The number of workflows that can be processed (that is, using the processor, not idle) at the same time across all Web front-end computers. | Workflow-eventdelivery-throttle: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262997(printer).aspx] |
| Workflow-eventdelivery-timeout | The time value a workflow job must run without the job timing out. | Workflow-eventdelivery-timeout: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc262968(printer).aspx] |

| | | |
|---|---|---|
| Workflow-timerjob-cpu-throttle | Obsolete. | Not applicable |
| Workitem-eventdelivery-batchsize | The paging size for events delivered to a single workflow instance. | Workitem-eventdelivery-batchsize: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263471(printer).aspx] |
| Workitem-eventdelivery-throttle | Specifies the maximum number of work items that can be obtained on a given query for runnable work items. | Workitem-eventdelivery-throttle: Stsadm property (Office SharePoint Server) [http://technet.microsoft.com/en-us/library/cc263141(printer).aspx] |